

Power Safety

UniVert2 Inverter

TYPE UniVert2	24 V/1,5 KVA G 24 E230/6,5/2rfg-CFp 1,5	110V/2,5 KVA G 110 E230/10,9/2rfg-CFp 2,5	220 V/3,3 KVA G 220 E230/14,4/2rfg-CFp 3,3
ENVIRONMENTAL			
Type of cooling	Forced air cooling		
Operation temperature range	0 °C to 45 °C, (measured below inverter)		
Storage temperature	-20 °C to +70 °C		
Environmental factors	IEC 721 part 3 – 3 class 3K3 / 3Z1 / 3B1 / 3C2 / 3S2 / 3M2		
Installation height	Up to 2000 m above sea level, at nominal load		
STANDARDS			
Interference emission	EN 55081-1 / EN 55022 class 'B'		
Interference resistance	EN 55082-2 / IEC 1000-4 part 2-5		
Low voltage function with safe disconnection	at Uin 24 Vdc in acc. to Vde 0100 part 41011.83 section 4.3.2/ EN 60950 section 2		
Approvals	CE		
Certification	ISO9001		

AEG is a registered trademark used under license from AB Electrolux

For further information
please refer to our website:

www.aegps.com

PERFECT IN FORM AND FUNCTION

AEG

Power Safety

UniVert2 Inverter

Modular inverter designed for industrial applications



Output Rating from a single inverter:
1.5 kVA (24 Vdc input)
2.5 kVA (110 Vdc input)
3.3 kVA (220 Vdc input)



PERFECT IN FORM AND FUNCTION

AEG

Power Safety

UniVert2 Inverter

Applications

The UniVert2 Inverter is especially designed for industrial voltages 24 V, 110 V and 220 V. It is used where the application requires the supply of AC loads from a secured DC busbar.

Communication

The UniVert2 offers full functionality in stand-alone mode, but additionally it can be controlled and monitored via the digital CAN-BUS, which is immune to interference. The control function is possible by the use of our control unit (PSM) which is available as an option.

Parallel operation

The UniVert2 can be paralleled up to a maximum of 8 units for increased power or the setting up of redundant systems using the n+1 principle.

Static bypass switch

To improve the System reliability the UniVert2 can be operated in parallel redundant mode, with a separate Static Bypass Switch (SBS) as an option. The SBS will change over to the mains with no break in case of (one or all) inverter disturbance. The separate SBS can also communicate with our optionally available central PSM (Power Supply Monitoring) control unit.

Operating principle

The unit is supplied by an external DC supply. The transistorised stack operates at a switching frequency of approx. 20 kHz and converts the DC voltage into a sine wave AC voltage. The output voltage of the UniVert2 will be finally formed by the use of an isolated transformer.

The transformer output voltage will be smoothed by an AC-filter, and connected to the output terminals via MCCB, current monitoring and the built-in output contactor. The controlled output of the inverter is short circuit proof and protected against voltage feedback by external loads and can also power capacitive, resistive and inductive loads. Non-linear loads with a high crest factor can also be supplied by the UniVert2.

Key features

- Overload capability up to 160 %
- High frequency stability
- Simple operation
- High efficiency
- Low inrush current
- Resistant to sustained short circuit and protected against power feedback by external loads
- Communication capable (CAN-BUS)
- SBS is available as an option
- Excellent dynamic behaviour
- Can operate in single mode and also parallel mode

TYPE UniVert2	24 V/1,5 KVA G 24 E230/6,5/2rfg-CFp 1,5	110V/2,5 KVA G 110 E230/10,9/2rfg-CFp 2,5	220 V/3,3 KVA G 220 E230/14,4/2rfg-CFp 3,3
Part number	3 000 000 602	3 000 000 263	3 000 000 601
INPUT			
Nominal input voltage	24 Vdc + 20 % - 15 %	110 Vdc + 20 % - 15 %	220 Vdc + 20 % - 15 %
Current consumption	62 A at 24 Vdc	20.4 A at 110 Vdc	14 A at 220 Vdc
Inrush current	≤ nominal input current		
Required DC input fuse	gL 80 A	gL 25 A	gL 20 A
OUTPUT			
Output (cos φ = 0,8)	1.5 KVA	2.5 KVA	3.3 KVA
Power factor range	0 ind. - 0 cap.		
Rated AC output voltage	230 Vac		
Deviation static / dynamic	± 0.5 % static, ± 3 % dynamic at 100 % load step		
Output Frequency	50 Hz ± 0.05 %		
Total Harmonic Distortion (THD)	< 3 %		
Efficiency, total	> 75 %	> 88 %	> 86 %
Overload behaviour	160 % for 1 minute / 130 % for 10 minutes, without switch-off		
Short circuit response	Resistant to sustained short circuit		
Parallel operation	Up to 8 inverters (with and without SBS)		
MONITORING AND INDICATION			
Monitoring	Output over-/ under-voltage, input-over-/ under-voltage, over temperature heatsink, overload, short circuit, self test of internal voltages		
Indicators	LCD for output voltage and current, LED for operation (green), LED inverter output OK (green), LED input under-voltage (red), LED input over-voltage (red), LED over-temperature (red), LED common alarm (red)		
Remote alarm	Potential free change over relay contact and LED indication		
Communication	Via digital CAN-BUS		
MECHANICAL			
Design	19"- plug-in module		
Ingress protection	IP 20		
Mechanical and vibration Stability	To EN 50178 part 9.4.3.2		
Equipment colour	RAL 7035 (Front)		
Dimensions W x H x D (mm)	483 x 177 x 460 (19" x 4 HU)	483 x 177 x 400 (19" x 4 HU)	483 x 177 x 460 (19" x 4 HU)
Weight	33 kg	39 kg	46 kg
DC-Input connection	10 ... 25 mm ²		
Screw terminals	0.5 ... 10 mm ²		
AC-Output	0.5 ... 10 mm ²		
Screw terminals	0.2 ... 2,5 mm ²		
Remote connection	M4 screw		
Screw terminals	10 respectively 16-pole spring contact		
Earthing connection	Optional (separate 19"-plug-in module Part Number 3 000 000 646)		
CAN-Bus-interface			
Static Bypass Switch 26.6 kVA			